

HIGH h CONVEYOR 2020™




PERFORMANCE

The High h Conveyor 2020 offers high-heat transfer rates for accelerated cooking, a small enough footprint to fit virtually any application, and does not require the energy consumption and higher HVAC needs of larger ovens.

VENTILATION

- UL (KNLZ) listed for ventless operation.[†]
- EPA 202 test (8 hr):
 - Product: Pepperoni Pizza
Results: 1.05 mg/m³
 - Product: Sandwiches
Results: 1.91 mg/m³
 - Ventless Requirement: <5.00 mg/m³
- Internal catalytic filtration to limit smoke, grease, and odor emissions.



1. Blower Motor
2. Impinged Air
3. Impingement Heater
4. Catalytic Converters (optional)
5. Conveyor Motor

EXTERIOR CONSTRUCTION

- 430 stainless steel front, top, sides and back
- Cool to touch covers and panels
- 7-inch capacitive touch screen with tempered glass cover

INTERIOR CONSTRUCTION

- Stainless steel interior
- 20-inch cook chamber

STANDARD FEATURES

- Simple and intuitive One-Touch controls with icons
- Small footprint with throughput exceeding other 28-inch conveyors
- Independently-controlled top and bottom air impingement
- Variable-speed High h recirculating impingement airflow system
- Stackable design up to 3 high (requires stacking kits)
- Variable-speed blower motors
- Idle mode for energy conservation
- Built-in self diagnostics for monitoring oven components
- Left or right feed conveyor belt direction via software
- Includes plug and cord (6 ft. nominal)
- Includes two 6" conveyor extensions
- Smart voltage sensor technology (U.S. only)
- Warranty – one year parts and labor
- Open Kitchen™ ready

CONNECTIVITY PART NUMBERS

- MDD-1001 - Initial equipment, two-way connectivity bundle
- MDD-1002 - Additional equipment, two-way connectivity bundle
- MDD-1003 - Additional year of subscription (PhD SAAS)

OPTIONAL FEATURES

- Split belt with individually-adjustable speed settings (split 50/50 and 70/30)
- Dual catalytic converters for ventless operation.[†]

CERTIFICATIONS



This product conforms to the ventilation recommendations set forth by NFPA96 using EPA202 test method.

[†] Ventless certification is for all food items except for foods classified as "fatty raw proteins." Such foods include bone-in, skin-on chicken, raw hamburger meat, raw bacon, raw sausage, steaks, etc. If cooking these types of foods, consult local HVAC codes and authorities to ensure compliance with ventilation requirements.

Ultimate ventless allowance is dependent upon AHJ approval, as some jurisdictions may not recognize the UL certification or application. If you have questions regarding ventless certifications or local codes please email ventless.help@turbochef.com

TurboChef reserves the right to make substitutions of components or change specifications without prior notice.

DOC-1078 / Rev Z / July 2025

DIMENSIONS

SINGLE UNITS

Height	17.0"	432 mm
Width	48.3"	1227 mm
Depth	35.9"	907 mm
Weight	195 lbs.	88.5 kg

Cook Chamber

Baking Area	2.8 ft ²	0.26 m ²
Belt Length	48.3"	1227 mm
Belt Width (Single)	20"	508 mm
Belt Width (50/50 Split)	9.5" / 9.5"	241 mm / 241 mm
Belt Width (70/30 Split)	15" / 4"	381 mm / 102 mm
Adjustable Opening (Min/Max)	1" / 3"	25 mm / 76 mm
Max Operating Temp	550°F	288°C
Bake Time Range	56 seconds to 15 minutes, 30 seconds	

Wall Clearance

Top	10"	254 mm
Sides	0"	0 mm
Back	0"	0 mm

ELECTRICAL SPECIFICATIONS - USA

Single: HCT-9500-501 / HCT-9500-501-V (Ventless)
50/50 Split: HCT-9500-504 / HCT-9500-504-V (Ventless)
70/30 Split: HCT-9500-507 / HCT-9500-507-V (Ventless)



NEMA 15-50P

Phase	3 Phase
Voltage	208/240 VAC
Frequency	50/60 Hz
Current Draw	40 Amp
Max Input	14.4 kW
Supply	4 Wire
Breakers	50 Amp

ELECTRICAL SPECIFICATIONS - CANADA

Single: HCT-9500-510-C / HCT-9500-510-C-V (Ventless)
50/50 Split: HCT-9500-511-C / HCT-9500-511-C-V (Ventless)
70/30 Split: HCT-9500-512-C / HCT-9500-512-C (Ventless)




UL 4 Pin, 60 A

Phase	3 Phase
Voltage	208/240 VAC
Frequency	50/60 Hz
Current Draw	40/46 Amp
Max Input	14.4 kW
Supply	4 Wire
Breakers	50/60 Amp

ELECTRICAL SPECIFICATIONS - EUROPE/ASIA (DELTA)

Single: HCT-9500-502-ED / HCT-9500-502-ED-V (Ventless)
50/50 Split: HCT-9500-505-ED / HCT-9500-505-ED-V (Ventless)
70/30 Split: HCT-9500-508-ED / HCT-9500-508-ED-V (Ventless)




IEC 4 Pin, 63 Amp

Phase	3 Phase
Voltage	220 - 240 VAC
Frequency	50/60 Hz
Current Draw	40 Amp
Max Input	14.4 kW
Supply	4 Wire
Breakers	50 Amp

ELECTRICAL SPECIFICATIONS - EUROPE/ASIA (WYE)

Single: HCT-9500-503-EW / HCT-9500-503-EW-V (Ventless)
50/50 Split: HCT-9500-506-EW / HCT-9500-506-EW-V (Ventless)
70/30 Split: HCT-9500-509-EW / HCT-9500-509-EW-V (Ventless)




IEC 5 Pin, 32 Amp

Phase	3 Phase
Voltage	380 - 415 VAC
Frequency	50/60 Hz
Current Draw	20 Amp
Max Input	14.4 kW
Supply	5 Wire
Breakers	32 Amp

ELECTRICAL SPECIFICATIONS - AUSTRALIA

Single: HCT-9500-520-AU / HCT-9500-520-AU-V (Ventless)
50/50 Split: HCT-9500-521-AU / HCT-9500-521-AU-V (Ventless)
65/35 Split: HCT-9500-522-AU / HCT-9500-522-AU-V (Ventless)



IEC 5 Pin, 32A

Phase	3 Phase
Voltage	380 - 415 VAC
Frequency	50/60 Hz
Current Draw	20 Amp
Max Input	14.4 kW
Supply	5 Wire

SHIPPING INFORMATION

U.S.: All ovens shipped within the U.S. are packaged in a double-wall corrugated box banded to a wooden skid.


International: All International ovens shipped via Air or Less than Container Loads are packaged in wooden crates.

Box size: 55" (1,397 mm) x 43" (1,092 mm) x 27" (686 mm)
Crate size: 58" (1,473 mm) x 46" (1,168 mm) x 28" (711 mm)
Item class: 110 NMFC #26710 HS code 8419.81


Approximate boxed weight: 300 lb. (136 kg)
Approximate crated weight: 410 lb. (186 kg)

Minimum entry clearance required for box: 27.5" (699 mm)
Minimum entry clearance required for crate: 28.5" (724 mm)


Front View



Side View



Top View



Stacked Views

